

SHEET NOTES

APPROXIMATE LOCATION FOR EXISTING ADDRESSABLE FIRE ALARM CONTROL PANEL TO REMAIN. DSA#03-113549. PROVIDE CONNECTION TO NEW FIRE ALARM DEVICES PER PLANS, UPDATE NEW FIRE ZONE MAP AND PROGRAM NEW DEVICES INFORMATION, MEASURE ACTUAL LOAD CURRENT AND VOLTAGE DROP FOR EACH NAC SIGNAL CIRCUITS, AND FACE STANDBY CURRENT AND ALARM CURRENT. SEND THE REPORT TO OWNER AND ENGINEER FOR

REVIEW, AND PLASTIC LAMINATED ONE COPY INSIDE FACP CABINET DOOR.

APPROXIMATE LOCATION FOR EXISTING FA NAC SIGNAL POWER BOOSTER PANEL. CONNECT NEW FA DEVICES PER PLANS. SEE FA PLAN E-3.

APPROXIMATE LOCATION FOR EXISTING PA/IC/TELEPHONE EQUIPMENT IN ADMIN OFFICE. CONNECT NEW SIGNAL DEVICES PER PLANS. SEE RISER

APPROXIMATE LOCATION FOR EXISTING COMPUTER IDF SERVER EQUIPMENT.
CONNECT NEW DATA OUTLETS PER PLANS. SEE RISER DIAGRAM 7/E-4.

APPROXIMATE LOCATION FOR EXISTING MASTER INTRUSION EQUIPMENT IN ADMIN OFFICE. CONNECT NEW INTRUSION ALARM DEVICES PER PLANS. SEE

RISER DIAGRAM 5/E-4.

EXISTING SIGNAL CONDUITS PATHWAY, FOR REFERENCE ONLY. PULL BACK NEW SIGNAL CABLES PER RISER DIAGRAMS ON DRAWING E-4. CONTRACTOR SHOULD INCLUDE ALLOWANCE IN HIS BID PROPOSAL TO FIELD VERIFY EXACT LOCATION AND REQUIREMENT PER PLANS.

(E) INDICATE EXISTING CONDUIT AND WIRING. FOR REFERENCE ONLY, FIELD VERIFY AS REQUIRED.

This document, the ideas and designs incorporated herein, as an instrument of Professional Service is the property of Integrated Designs by SOMAM Inc. and is not to be used, in whole or in part for any other project without written authorization © COPYRIGHT 2017

Ownership of Documents

ESIGN - CONSTRUCTION MANAGEMENT

- Fresno, California 93710

56-0887 E-Mail: design@comam.com

Idesigns.com

Revision Description:

Rev. Date:

WIRING. FOR REFERENCE ONLY,

PROJECT NOTES

- A. EXISTING ELECTRICAL SERVICE HAS BEEN INVESTIGATE AND FOUND TO HAVE ADEQUATE CAPACITY FOR THE PROPOSED LOAD ADDITION AS SHOWN ON THESE PLANS
- B. SOURCE OF POWER HAS BEEN INVESTIGATED AND IS
- ADEQUATE FOR THE ADDITIONAL LOAD.

 C. SITE INSPECTOR IS TO WITNESS AND VERIFY GROUNDING
- D. CONTRACTOR TO MONITOR EXISTING FIRE ALARM SYSTEM IF IT IS INTERRUPTED OR DISCONNECTED.



R EL ATAB

PIONEI 1 RELO

MEP COMPONENT ANCHORAGE NOTES

ALL MECHANICAL, PLUMBING, AND ELECTRICAL COMPONENTS SHALL BE ANCHORED AND INSTALLED PER THE DETAILS ON THE DSA APPROVED CONSTRUCTION DOCUMENTS. WHERE NO DETAILS IS INDICATED, THE FOLLOWING COMPONENTS SHALL BE ANCHORED OR BRACED TO MEET THE FORCE AND DISPLACEMENT REQUIREMENTS PRESCRIBED IN THE 2016 CBC, SECTIONS 1616A.1.18 THROUGH 1616A. 1.26 AND ASCE 7-10 CHAPTER 13, 26 AND 30

ALL DEDMANENT FOLIDMENT AND COMPONENTS

ALL PERMANENT EQUIPMENT AND COMPONENTS.
 TEMPORARY OR MOVABLE EQUIPMENT THAT IS PERMANENTLY ATTACHED (E.G. HARD WIRED) TO THE BUILDING UTILITY SERVICES SUCH AS ELECTRICITY, GAS OR WATER.

3. MOVABLE EQUIPMENT WHICH IS STATIONED IN ONE PLACE FOR MORE THAN 8 HOURS AND HEAVIER THAN 400 POUNDS ARE REQUIRED TO BE ANCHORED WITH TEMPORARY ATTACHMENTS.

THE ATTACHMENT OF THE FOLLOWING MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE, BUT NEED NOT BE DETAILED ON THE PLANS. THESE COMPONENTS SHALL HAVE FLEXIBLE CONNECTIONS PROVIDED BETWEEN THE COMPONENT AND ASSOCIATED DUCTWORK, PIPING, AND CONDUIT.

A. COMPONENTS WEIGHING LESS THAN 400 POUNDS AND HAVE A CENTER OF MASS LOCATED 4 FEET OR
LESS ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT.
 B. COMPONENTS WEIGHTING LESS THAN 20 POUNDS, OR IN THE CASE OF DISTRIBUTED SYSTEMS, LESS THAN
5 POUNDS PER FOOT, WHICH ARE SUSPENDED FROM A ROOF OR FLOOR OR HUNG FROM A WALL.

FOR THOSE ELEMENTS THAT DO NOT REQUIRE DETAILS ON THE APPROVED DRAWINGS, THE INSTALLATION SHALL BE SUBJECT TO THE APPROVAL OF THE STRUCTURAL ENGINEER OF RECORD AND THE DSA DISTRICT STRUCTURAL ENGINEER. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH ABOVE REQUIREMENTS.

PIPING, DUCTWORK, AND ELECTRICAL DISTRIBUTION SYSTEM BRACING NOTE

PIPING DUCTWORK, AND ELECTRICAL DISTRIBUTION SYSTEMS SHALL BE BRACED TO COMPLY WITH THE FORCES AND DISPLACEMENTS PRESCRIBED IN ASCE 7-10 SECTION 13.3 AS DEFINED IN ASCE 7-10 SECTION 12.6.8, 13.6.5.6 AND 2016 CBC, SECTION 1616A.1.23, 1616A.1.24, 1616A.1.25 AND 1616A.1.26.

THE METHOD OF SHOWING BRACING AND ATTACHMENTS TO THE STRUCTURE FOR THE IDENTIFIED DISTRIBUTION SYSTEM ARE AS NOTED BELOW. WHEN BRACING AND ATTACHMENT ARE BASED ON A PREAPPROVED INSTALLATION GUIDE (E.G., SMACNA OR OSHPD OPM), COPIES OF THE BRACING SYSTEM INSTALLATION GUIDE OR MANUAL SHALL BE AVAILABLE ON THE JOBSITE PRIOR TO THE START OF AND DURING THE HANGING AND BRACING OF THE DISTRIBUTION SYSTEMS. THE STRUCTURAL ENGINEER OF RECORD SHALL VERIFY THE ADEQUACY OF THE STRUCTURE TO SUPPORT THE HANGER AND BRACE LOADS.

MECHANICAL PIPING (MP), MECHANICAL DUCTS (MD), PLUMBING PIPING (PP), ELECTRICAL DISTRIBUTION SYSTEM (E):

MP MD PP E - OPTION 1: DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES AND DETAILS.

MP MD PP E - OPTION 2: SHALL COMPLY WITH THE APPLICABLE OSHPD PRE-APPROVAL (OPM #)

MP MD PP

#_____OPTION 3: SHALL COMPLY WITH SMACNA SEISMIC RESTRAINT MANUAL, OSHPD

OPTION 3: SHALL COMPLY WITH SMACNA SEISMIC RESTRAINT MANUAL, OSHPD EDITION (2009), INCLUDING ANY ADDENDA, FASTENERS AND ATTACHMENTS NOT SPECIFICALLY IDENTIFIED IN THE SMACNA SEISMIC RESTRAINT MANUAL, OSHPD EDITION, ARE DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES AND DETAILS. THE DETAILS SHALL ACCOUNT FOR THE APPLICABLE SEISMIC HAZARD LEVEL _____ AND CONNECTION LEVEL _____ FOR THE PROJECT AND CONDITIONS.

Agency Approval Stamp:

FILE #:_

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES

03-118271

AC__FLSSTMSS_OL

TRACKING #: DSA TRACKING NO

Stamp(s):

Job No.: **5289**

Sheet No.:

JOHN CHONG ENGINEERS

JOHN S. CHONG
E 14419

EXP.6/30/2018

(559) 915-9368 • FAX 291-940

j ceng i neer@do l.com