

2 TYPICAL REFLECTED CEILING PLAN

- SHEET NOTES -

1 WALL HUNG HVAC UNIT

2 THERMOSTAT @ +60" SEALED

3 MAIN RUNNER TYP

4 CROSS RUNNER TYP

5 INTERIOR LIGHT FIXTURE REFER TO SHEET SHEET E1 FOR SPEC'S

6 CEILING HEIGHT @ 8'-6" NOM

7 SPLAY WIRE SEE 4/M2 FOR DETAILS

8 FIXED CEILING END

9 FREE CEILING END

CENTER SECTION THAT CROSSES

MODULE LINE TO BE FIELD INSTALLED

 $\langle 11 \rangle$ NOT USED

(12) CONCEALED SUPPLY AIR DUCT ABOVE T-BAR CEILING

TYPICAL 4-WAY SUPPLY AIR REGISTER LOCATION AND SIZE MAY VARY PER CEILING LAYOUT AND BUILDING SIZE

NOTE:

WHERE TWO OR MORE HVAC UNITS SERVE A COMMON SPACE, UNITS SHALL BE EQUIPED WITH DUCT SMOKE DETECTOR FOR AUTO SHUTDOWN. INTERCONNECT WITH FIRE ALARM SYSTEM

AUTOMATIC SHUT-OFF IS NOT REQUIRED WHEN ALL OCCUPIED ROOMS SERVED BY THE AIR HANDLING EQUIPMENT HAVE DIRECT ACCESS TO THE EXTERIOR AND THE TRAVEL DISTANCE DO NOT EXCEEDS 100 FT. PER CMC 609 EXEPTION #2

BASED ON PC 02-109695

REVISIONS

NO DATE DESCRIPTION

A

A

A

DATE: 08/12/10

SCALE: NOTED

DRAWN BY: RS

SERIAL NO.:


CUSTOMER:


BAKERSFIELD CITY SCHOOLS


24' x 40' RELOCATABLE BUILDINGS TYPICAL REFLECTED CEILING PLAN



APPROVALS:









PROJECT No.