



AR FILIER: SEE GEN. MOTES ON ARCHIE SHEET OF PLANS

HVAC MOUNTING SCALE: 3/8" - 1'-8"



DUCT MOUNTING



REGISTER BOX DETAIL


EQUIPMENT & MATERIAL SCHEDULE

HEAT PUMP BARD WALLMOUNT, WH421-LA08VX4, OR EQUIV.
41,500 NOM. BTUH COOLING CAPACITY
41,000 NOM. BTUH HEATING CAPACITY FROM COMPRESSOR
OR 27,300 NOM. BTUH HEATING CAPACITY FROM HEAT STRIP MCA 46, MOCP 50, 1500 CFM @ .3 ESP, UNIT WEIGHT 510 LB. 230 VOLT, 60 CYCLE, SINGLE PHASE


INTERIOR DUCTWORK- FLEX DUCT W/ 1" INSULATION- CLASS I U.L.-181 FLAME SPREAD - 15 SMOKE DEVELOPED - 25

<u>LEGEND</u>

THERMOSTAT - WHITE ROGERS 1F92-71
MOUNT AT +48" A.F.F.



EXHAUST FAN (BROAN #670 OR EQUAL) 50 CFM



MECHANICAL NOTES

ROUND FLEX DUCT SHALL BE 'GLASS FLEX' ABL-181 OR EQUAL U.L. LISTED CLASS I FLEXIBLE DUCT WITH 13/16" THICK FIBERGLASS INSULATION. NON-PERFORATED LINER AND ADJUSTABLE SHEET METAL COLLARS.

THERMOSTAT PROGRAMMING TO BE PERFORMED AND BATTERY PROVIDED BY OTHERS ON SITE. TEST AND BALANCE OF HVAC SYSTEM TO BE PROVIDED AND PERFORMED BY OTHERS ON SITE. ALL HVAC EQUIPMENT LEAVES FACTORY WIRED FOR 240V. OPERATION. THE ACCEPTABLE OPERATING RANGE FOR THE 240 & 208 TAPS ARE: TAP RANGE 2**4**0 208

253-216 220-187 MECHANICAL PLAN

LICENSE EXPIRES 6-30-9000 1 0 0 1 1 8 ... DATE 12-8-97 DRAWN BY R.D.L. SCALE APPROVED REVISIONS DIV. OF THE STATE ARCHITECTS
OFFICE OF REGULATION SERVICES
ACT TO 0 0 7 3
ACT TIS 16 38 SHEET NO.

THIS DRAFT OF DIRECTION ARE TO DIRECTION WHOLE OR PART ON WATERIAL IN MATERIAL IN MATERIAL