

- KEY NOTE	S-
------------	----

- 1 4x4x5/16 HSS COLUMN
- 2 FLOOR BEAM PER SCHEDULE
- 3 10 GA. LONGITUDINAL ROOF CHANNEL 14"-18"-14" @ DOUBLE SLOPE 14"-22" @ SINGLE SLOPE
- 4 12 GA. TRANSVERSE ROOF CHANNEL 14" MIN 22" MAX
- 6" Ø MAX OPENING IN WEB OF ROOF BEAM WITHOUT WEB REINFORCEMENT MINIMUM SPACING OF HOLES @ 48" O.C. HOLES MAY OCCUR @ ANY LOCATION ALONG LENGTH OF ROOF BEAM EXCEPT AS NOTED OTHERWISE ON FRAMING ELEVATION NOTE: IF HOLE IS 3" OR LESS THEY MAY BE SPACED AT 24"O.C. MINIMUM
- 4" Ø MAX OPENING IN WEB OF FLOOR BEAM WITHOUT WEB REINFORCEMENT MINIMUM SPACING OF HOLES @ 48" O.C. HOLES MAY OCCUR @ ANY LOCATION ALONG LENGTH OF FLOOR BEAM WITH DIRECT FOUNDATION SUPPORT BELLOW. OPENINGS ARE NOT ALLOWED WHERE BEAMS ARE SPANNING BETWEEN FOUNDATIONS OR ACROSS VENT OPENINGS.
 - NOTE: IF HOLE IS 2" OR LESS THEY MAY BE SPACED AT 24" MINIMUM
- 7 14 GA OUTRIGGER CHANNEL AT OPTIONAL ENCLOSED OVERHANG REFER TO DETAIL 1/S4A
- 8 2x6 H.F. #2 OR BETTER STUDS @ 16" O.C.
- 9 12"x 30" MAX OPENING ALLOWED ONLY
 AT EXTERIOR BEAMS WITH A WALL DIRECTLY
 BELOW. IF WALL BELOW IT IS REMOVED THEN
 A COLUMN MUST BE ADDED AT MID SPAN.
 REFER TO DETAIL 4/S4A FOR OPENING
 REINFORCEMENT

SUBFLOOR TYPE	FLOOR BEAM SIZE	ALTERNATES
VIROC OR PLYWOOD	C7x9.8	C9x13.4, C10x15
CONCRETE	C9x13.4	C10x15.3

REVISIONS				
NO	DATE	DESCRIPTION		
A				
2				
3			Nesen use (III 18 50 Pertendent have de de Tray (tray for de historium use se del Tributa (tray for an entre e	
4				

DATE: 02/25/08

SCALE: NOTED

DRAWN BY: DM


SERIAL NO.:


CUSTOMER:

12' × 40' RELOCATABLE BUILDINGS

TYPICAL FRAME ELEVATIONS







IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
OFFICE OF REGULATION SERVICES

PC 02-109808

AC. FLS SS

DATE 4/109

81

PROJECT No.